

Declaration of Performance

Nr. ABC04-3290841.1



1. Unique identification code of the product type

Product number: 3290841
red masonry KMZ ungelocht 28-2,2
215x102,5x65 mm
Product name: Richmond red smooth (Solid)

2. Usage

U masonry, Category I, Load-bearing and non-load-bearing
protected and unprotected masonry

3. Manufacturer

Recker Ziegelwerk
Berentelg & Hebrok OHG
Mettinger Str. 135
D - 49509 Recke

4. System of assessment and verification of constancy of performance

System 2+

5. Harmonized standard: EN 771-1:2011+A1:2015

Notified body: NB 2510

6. Declared performance(s):

Essential characteristics		Performance
Dimensions	Length/Width/Height (mm)	215x102,5x65
Limiting error	Category	Tm (L +5/-10,B +/-5,H +/-3)
Dimensions span	Category	Rm (L 10,B 6,H 4)
Form and shape	Form and property	Form a, Abs. 5.3.2
Compressive strength	Category	Category I bricks
	Medium compressive strength (N/mm ²)	≥ 44
	Load direction	perpendicular to the bed joint
Usual moisture expansion	(mm/m)	NPD
Bond strength	(N/mm ²)	NPD
Content of soluble salts	Bracket	S2
Fire behavior	Euro class	A1
water absorption	(M-%)	≤ 6
Water vapor permeability	(μ)	50/100
Airborne sound insulation		NPD
Gross dry density	Average (kg/m ³)	2100
	Tolerances	D2
Net dry density	Average (kg/m ³)	2200
	Tolerances	D2
Thermal Conductivity	(W/mK)	NPD
Resistance to frost	Bracket	F2
Dangerous substances		NPD

The performance of the identified product corresponds to the set of declared performance (s). The manufacturer specified above is solely responsible for drawing up this declaration of performance in accordance with Regulation (EU) No. 305/2011.

Signed for and on behalf of the manufacturer by:

H. Berentelg
executive Director

Recke, 28.04.2020