

CREST NELSKAMP ROOFING TILES

F8.5 clay pantile



F8.5 in
Red Brown
(202)



crest
NELSKAMP
ROOFING TILES

t: 01430 432667

www.crest-bst.co.uk

e: info@crest-bst.co.uk

Manufactured to comply with the requirements of EN1304 European Standard for Clay Roof Tiles

F8.5 A large format lightweight clay pantile

▶ High quality clay tiles ▶ Minimum roof pitch 10° ▶ Economical ▶ Large range of colours

H14 Technical details

Length	499 mm
Width	344 mm
Gauge	370 - 405mm
Cov' Width (mm)	297 ± 2.0
Min' roof pitch	10°
No. of tiles per m ²	8.4
Weight per tile	4.6 kg
Weight per m ² (min.)	38.6 kg
Battens per m ² (min)	3.4
Batten size (mm)	50 x 25
Fixing	Clipped

Fittings: A wide choice of fittings are available including these below



Low roof pitches 17°-10°

F8.5 is the perfect interlocking large clay pantile for low-pitch roofs, we recommend that these fixing practices are followed:

- Lay F8.5 tiles straight bond.
- Headlap minimum 100mm.
- Use appropriate air and vapour permeable underlay, which does not require secondary roof ventilation.
- Lay the roof underlay to the manufacturer's instructions.
- Maximum rafter length 6m.
- All tiles are to be clipped with purpose-made tile clips, reference 409/213
- Roof perimeters including around roof windows must be securely fixed to BS 5534
- All areas around the roof perimeter and abutments must be properly finished as well as any areas around any 'velux type' windows (These are the areas where potential problems are likely to occur on a low roof pitch.)

The F8.5 range of colours



For more information on the F8.5 Tile or to order a sample call us on **01430 432667**